



# DIAMOND CLASSIC TELEPHONES

Enjoy the convenience of an integrated speakerphone and up to eleven guest service buttons.

- **Single and Two-Line Telephone**
- **Integrated Speakerphone** – Hands-free conversations\*
- **Guest Service Buttons** – Up to ten (10) for one-touch access to hotel services
- **ADA Handset Volume Boost** – Three (3) distinct levels, compliant with HAC/VC and FCC requirements
- **Raised Red Message-Waiting Lens** – Easily seen from any area in the guestroom
- **Patented MultiX™ Message-Waiting Circuitry** – Guarantees operation of up to 10 phones for suite applications, with an extra-bright message-waiting lamp
- **Mute Key** – Deactivates microphone during speakerphone and handset calls; a red LED indicates activation\*\*
- **Speaker On/Off Key** – With red LED for easy speakerphone activation\*
- **PrimeLine™/RingLine Select** automatically selects the available/ringing line.\*\*\*
- **Electronic 3-way Call Conference Function** with LED indicator for convenient multi-line conversations\*\*\*
- **Hold Key** – Places the active line on hold so the second line can be used or a conference call initiated\*\*\*
- **Hold Release Detection Circuit** – Releases calls on hold when line is accessed by any telephone
- **Redial Key** – Automatically redials the last number dialed, with timed deletion (most models)
- **Flash Key** (most models)
- **Textured Finish** – Provides durable resistance against scratches and smudges
- **Full-Length Paper Faceplate** – Allows user-friendly customization
- **Desk or Wall Mountable** – Provides placement flexibility
- **Hidden Programming Key** – Eliminates arbitrary reprogramming of autodial keys
- **Data Port** – Easy access for laptop modem or fax machine use

\*Speakerphone models only

\*\*Not available in single-line basic or lobby phone

\*\*\*Two-line only

## THE TELEDEX DIAMOND SERIES

### SPECIFICATIONS

<b>Standard Colour:</b> . . . . .	Ash and Black	<b>FCC Specifications:</b> . . . . .	Meet or exceeds Part 15, Subpart J, Class A, Part 68	<b>Ringer Equivalence:</b> . . . . .	Z
<b>Footprint:</b> . . . . .	6.25" x 9.0"	<b>Safety Standard:</b> . . . . .	ETL and CE	<b>Cabling:</b> . . . . .	2 pair minimum
<b>Weight:</b> . . . . .	2.3 lbs.	<b>Operating Voltage:</b> . . . . .	24 to 56 VDC Non-Polarity	<b>Registered Connector:</b> . . . . .	USOC RJ-14
<b>Packaging:</b> . . . . .	12 per carton	<b>Signaling:</b> . . . . .	Standard 12 tone DTMF/Pulse	<b>Handset:</b> . . . . .	Hearing Aid compatible Standard "K" or Euro type
<b>Faceplate Size:</b> . . . . .	8.75" x 3.13"	<b>Flash Timing:</b> . . . . .	600 ms	<b>Handset Cord:</b> . . . . .	10-foot coil cord
				<b>Line Cord:</b> . . . . .	15-foot, 2 pair

### Part Numbers

#### Diamond Lobby

DIA 65009 . . . . .	Ash
DIA 650091 . . . . .	Black

#### Diamond Basic

DIA 65309 . . . . .	Ash
DIA 653091 . . . . .	Black

#### Diamond +

DIA 65039 . . . . .	Ash
DIA 650391 . . . . .	Black

#### Diamond +3

DIA 65739 . . . . .	Ash
DIA 657391 . . . . .	Black

#### Diamond +5

DIA 65139 . . . . .	Ash
DIA 651391 . . . . .	Black

#### Diamond +10

DIA 65239 . . . . .	Ash
DIA 652391 . . . . .	Black

#### Diamond +s-3

DIA 65749 . . . . .	Ash
DIA 657491 . . . . .	Black

#### Diamond +s-5

DIA 65149 . . . . .	Ash
DIA 651491 . . . . .	Black

#### Diamond +s

DIA 65339 . . . . .	Ash
DIA 653391 . . . . .	Black

#### Diamond +s-5

DIA 65039 . . . . .	Ash
DIA 650391 . . . . .	Black

#### Diamond L2-E

DIA 67059 . . . . .	Ash
DIA 670591 . . . . .	Black

#### Diamond L2-5E

DIA 67159 . . . . .	Ash
DIA 671591 . . . . .	Black

#### Diamond L2-10E

DIA 67259 . . . . .	Ash
DIA 672591 . . . . .	Black

#### Diamond L2s-5E

DIA 67149 . . . . .	Ash
DIA 671491 . . . . .	Black

#### Diamond L2s-10E

DIA 67359 . . . . .	Ash
DIA 673591 . . . . .	Black

