

COMMODORE™ DUO



Innovation in interim and deep carpet extraction.

Several uses from one machine, the Commodore™ DUO is the pragmatic choice. With just the turn of a switch, easily change from extraction to interim cleaning. Make room for more storage by replacing two machines with one, or improve your cleaning process by adding productive interim cleaning to the mix. Interim cleaning extends the time between scheduled deep extractions and improves your carpets appearance. This machine operates at only 63 dBA which is perfect for daytime cleaning.

Several uses for one machine

- Extraction and interim cleaning in one machine

Functional design

- On-board accessory wand for detail work

COMMODORE DUO

TECHNICAL SPECIFICATIONS

Cleaning path/width	in	20
Solution/recovery capacity	gal	19/17
Practical productivity - restorative/interim	sq.ft/hr	13,200/6,000
Operating noise level	dBA	63/71
Max operating speed - restorative/interim	mph	0.63/1.25
Transport speed	mph	2.9
Vacuum	hp. stage	.75 HP, 3
Water lift	in	83.1
Pump pressure	psi	100
Flow rate - restorative/interim	gpm	1.05/0.25
Weight without batteries	lbs	340
Dimensions (L x W x H)	in	54 x 27 x 43

EQUIPMENT

Order No.	Description
1.008-002.0	Commodore™ DUO, 36 V/130 Ah wet batteries, 21A C50 automatic charger
1.008-000.0	Commodore DUO, 36 V/195 Ah batteries, 21A C50 automatic charger
1.008-004.0	Commodore™ DUO, 36 V/234 Ah AGM batteries, 21A dual mode automatic charger